


Oct.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- Note 1. Per pack : 100 pieces.
 2. This product satisfies halogen free requirements defined as 900ppm maximum chlorine, 900ppm maximum bromine, and 1500ppm maximum total of chlorine and bromine.
 3. Rerer to the technical specification (ETAP-H1051-00) for the packing type.
 4. Please make sure refer to the manuals below for operation of this product.
 For Cable assembly procedure ETAD-H0995-00
 For Operation Manual ETAD-H0996-00

NO.		MATERIAL		FINISH . REMARKS		1	PA 9T	BLACK, UL94V-0		
UNITS mm		SCALE 10: 1		COUNT		DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA		20200710		DRAWING NO.		EDC-380639-00-00		
		CHECKED : ST. WADA		20200710		PART NO.		DF53-14P-0. 6C		
		DESIGNED : TH. SATO		20200710		CODE NO.		CL668-1021-0-00		
		DRAWN : TH. SATO		20200710						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[DF53-14P-0.6C](#)