


Oct.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- 注 1. Per pack: 100 pieces.
2. A number of slits varies depending on pin count.
 - 2 slits for 2 to 12 pos. (No. 1, No. N)
 - 4 slits for 14 to 20 pos. (No. 1, No. 4, No. N-3, No. N)
3. This product satisfies halogen free requirements defined as 900 ppm maximum chlorine, 900 ppm maximum bromine, and 1500 ppm maximum total of chlorine and bromine.
4. Refer to the technical specification (ETAP-H1051-00) for the packing type.
5. Please make sure refer to the manuals below for operation of this product.
 For cable assembly procedure ETAD-H0995-00
 For operation manual ETAD-H0996-00

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	10:1	0				2023.03.29
APPROVED : SJ. OKAMURA 2024.06.21			DRAWING NO. EDCX-407144-00-00			
CHECKED : SJ. OKAMURA 2024.06.21			PART NO. DF53-P-0.6C			
DESIGNED : JN. TONAI 2024.06.21			CODE NO. CL0010-0636-0-00			
DRAWN : JN. TONAI 2024.06.21						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[DF53-4P-0.6C](#)